

15 AMP MINIATURE PC BOARD RELAY

FEATURES

- High performance
- Low seated height
- Flux tight and sealed versions available
- UL, CUR file E43203
- Class B insulation (130°C) standard



CONTACTS

Arrangement	SPST (1 Form A) SPDT (1 Form C)
Ratings	Form A and C Max. switched power: 210 W or 2770 VA Max. switched current: 15 A AC, 7 A DC Max. switched voltage: 30 VDC or 300 VAC
UL/CUR Ratings	1 Form A 15 A at 125 VAC, general use 10A at 277 VAC, general use, 100,000 cycles TV - 5 120 VAC 1 Form C 10 A at 277 VAC, general use, 100,000 cycles
Material	AgSnO ₂
Resistance	< 100 milliohms initially (24 V, 1 A method)

COIL

Power At Pickup Voltage Max Continuous Dissipation	203 mW 1.0 W at 20°C (68°F)
Temperature Rise (at nominal coil voltage)	27°C (49°F)
Temperature	Max. 130°C (266°F)

NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Unsealed relays should not be dip cleaned.
4. Specifications subject to change without notice.

GENERAL DATA

Life Expectancy Mechanical Electrical	1 x 10 ⁶ 1 x 10 ⁵ at rated load
Operate Time	10 ms max.
Release Time	5 ms max. (with no coil suppression)
Dielectric Strength (at sea level for 1 min.)	1500 Vrms contact to coil 1000 Vrms across contacts
Insulation Resistance	100 megohms min. at 500 VDC, 50% RH
Dropout	Greater than 10% of nominal coil voltage
Ambient Temperature Operating Storage	At nominal coil voltage -40°C(-40°F) to 95°C(203°F) -40°C(-40°F) to 130°C(266°F)
Vibration	0.062" DA at 10–55 Hz
Shock	10 g
Enclosure	P.B.T. polyester
Terminals	Tinned copper alloy, P.C.
Max. Solder Temp.	270°C (518°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	10 g

ZETTLER electronics

Logistic Design (UK) Limited. Unit 3, Eagle Centre Way, Luton LU4 9US www.zettlerrelay.com sales@zettlerrelay.com
Telephone +44 (0) 1582 599 600 Fax +44 (0) 1582 599 700


AZ943

RELAY ORDERING DATA

STANDARD RELAYS					
COIL SPECIFICATIONS				ORDER NUMBER	
Nominal Coil VDC	Max. Continuous VDC	Coil Resistance $\pm 10\%$	Must Operate VDC	Unsealed	Sealed
5	8.3	70	3.8	AZ943-1CH-5D	AZ943-1CH-5DE
6	10.0	100	4.5	AZ943-1CH-6D	AZ943-1CH-6DE
9	15.0	225	6.8	AZ943-1CH-9D	AZ943-1CH-9DE
12	20.0	400	9.0	AZ943-1CH-12D	AZ943-1CH-12DE
18	30.0	900	13.5	AZ943-1CH-18D	AZ943-1CH-18DE
24	40.0	1,600	18.0	AZ943-1CH-24D	AZ943-1CH-24DE
48	67.0	6,200	36.0	AZ943-1CH-48D	AZ943-1CH-48DE

Substitute "1AH" in place of "1CH" to indicate 1 Form A contact.

MECHANICAL DATA



Dimensions in inches with metric equivalents in parentheses. Tolerance: $\pm .010$ "