

C&K 7000 Series Miniature Toggle Switches




Features/Benefits

- **Multi-pole and multi-position**
- **Wide variety of actuator and termination options**
- **Epoxy sealed terminals prevent contamination during soldering**

Typical Applications

- **Telecommunications**
- **Instrumentation**
- **Medical equipment**



A

Toggle

Build-A-Switch

Our easy Build-A-Switch concept allows you to mix and match options to create the switch you need. Below is a complete listing of options shown in catalog. To order, simply select desired option from each category and place in the appropriate box. Switches with standard options are shown on pages A-4 and A-5. Available options are shown and described on pages A-6 thru A-18. For additional options not shown in catalog, consult our Customer Service Center.

Typical Example: 7 1 0 1 — S — — — Y — — — Z — — — Q — E — — — —

Switch Function

7101 (STD.) SP On-None-On
7103 (STD.) SP On-Off-On
7201 (STD.) DP On-None-On
7203 (STD.) DP On-Off-On
7211 (STD.) DP On-On-On
7301 (STD.) 3P On-None-On
7401 (STD.) 4P On-None-On
7105 SP Mom.-Off-Mom.
7107 SP On-Off-Mom.
7108 SP On-None-Mom.
7109 SP None-On-Mom.
7205 DP Mom.-Off-Mom.
7207 DP On-Off-Mom.
7208 DP On-None-Mom.
7209 DP None-On-Mom.
7213 DP On-On-Mom.
7215 DP Mom.-On-Mom.
7303 3P On-Off-On
7305 3P Mom.-Off-Mom.
7307 3P On-Off-Mom.
7308 3P On-None-Mom.
7309 3P None-On-Mom.
7403 4P On-Off-On
7405 4P Mom.-Off-Mom.
7407 4P On-Off-Mom.
7408 4P On-None-Mom.
7409 4P None-On-Mom.
7411 4P On-On-On
7413 4P On-On-Mom.
7415 4P Mom.-On-Mom.

Actuator

M (STD.) .200" high
P3 (STD.) Flatted, anti-rotation, .450" high
S (STD.) .410" high
T (STD.) .687" high, 15/32 bushing
K2 Locking lever, .704" high
K9 Locking lever, .704" high
K12 Locking lever, .732" high
K19 Locking lever, .732" high
L .840" high
L1 .640" high
L1P Anti-rotation, .640" high
L2 .550" high
L2P Anti-rotation, .550" high
L3 Plastic, .840" high
L3P Plastic, anti-rotation, .840" high
L40 Lever handle without cap
L41 Lever handle with cap
L42 Lever handle with cap
LP Anti-rotation, .840" high
MP Anti-rotation, .200" high
P1 Flatted, anti-rotation, .840" high
P4 Flatted, anti-rotation, .250" high
SP Anti-rotation, .420" high
T1 .460" high, 15/32 bushing
T1P Anti-rotation, .460" high, 15/32 bushing
T2P Flatted, anti-rotation, .610" high, 15/32 bushing,
TP Anti-rotation, .687" high, 15/32 bushing

Bushing

D (STD.) .280" high, keyway
H (STD.) .296" high, flat
Y (STD.) .350" high, keyway
NONE No bushing
CW Splashproof
D8 .280" high, flat
D9 .280" high, keyway
H3 .315" high, keyway
H4 8mm high, keyway
Y1 .378" high, keyway
Y3 8.9mm high, keyway
Y4 .378" high, flat
Y9 .350" high, keyway

Terminations

A (STD.) Right angle, PC thru-hole
AV2 (STD.) Vert. right angle, PC thru-hole
C (STD.) PC Thru-hole
V3 (STD.) .460" high, V-bracket
Z (STD.) Solder lug
A2 Right angle, PC thru-hole
A3 Right angle, PC thru-hole
A4 Right angle, PC thru-hole
A7 Right angle, PC thru-hole
AV3 Vert. right angle, PC thru-hole
AW Right angle, extended, PC thru-hole
AW1 Right angle, extended, PC thru-hole
AW3 Right angle, extended, PC thru-hole
AW4 Right angle, extended, PC thru-hole
R Right angle with PCB
R2 Right angle with PCB
V2 .555" high, V-bracket
V4 .630" high, V-bracket
V6 .460" high, V-bracket
V7 .630" high, V-bracket
V8 .953" high, V-bracket
V9 1.150" high, V-bracket

Contact Material

B (STD.) Gold
Q (STD.) Silver Seal
K Gold **E** (STD.) Epoxy
M Silver **I** Epoxy potted
G Gold over silver base
L Gold over silver

Actuator Color/Finish

NONE (STD.) Finish
0 (STD.) Actuator finish with black bushing

1 White
2 Black
3 Red
7 Blue
S Satin chrome

Bushing Finish

NONE (STD.) Nickel on all bushings (except D8, satin chrome)

KXX Actuator Color/Finish

NONE (STD.) Natural aluminum
0 (STD.) Natural aluminum with black bushing
2 Black anodized aluminum
3 Red anodized aluminum
7 Blue anodized aluminum

V21 .555" high, snap-in V-bracket
V31 .460" high, snap-in V-bracket
V41 .630" high, snap-in V-bracket
V61 .460" high, snap-in V-bracket
V71 .630" high, snap-in V-bracket
V81 .953" high, snap-in V-bracket
V91 1.150" high, snap-in V-bracket
W .750" long, wire wrap
W1 .964" long, wire wrap
W3 .425" long, wire wrap
W4 1.062" long, wire wrap
W5 1.305" long, wire wrap
Z3 Quick connect

Note: UL/CSA models available, see page A-6.

C&K 7000 Series Miniature Toggle Switches

Specifications

CONTACT RATING: B contact material: 0.4 VA max. @ 20 V AC or DC max. Q contact material: 5 AMPS @ 120 V AC or 28 V DC; 2 AMPS @ 250 V AC. See page A-18 for additional ratings.

ELECTRICAL LIFE: 7X01 and UX1 models: 100,000 make-and-break cycles at full load. All other models: 40,000 cycles.

CONTACT RESISTANCE: Below 10 milliohms typ. initial @ 2-4 V DC, 100 mA, for both silver and gold plated contacts.

INSULATION RESISTANCE: 10^9 ohms min.

DIELECTRIC STRENGTH: 1000 V RMS min. @ sea level.

OPERATING TEMPERATURE: -30°C to 85°C .

SOLDERABILITY: Per MIL-STD-202F method 208D, or EIA RS-186E method 9 (1 hour steam aging).

NOTE: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.

Materials

CASE: Glass filled nylon 6/6, flame retardant, heat stabilized, or diallyl phthalate (DAP) (UL 94V-0).

ACTUATOR: Brass, chrome plated.

BUSHING: Brass or zinc, nickel plated.

HOUSING: Stainless steel.

SWITCH SUPPORT: Brass or steel, tin plated.

END CONTACTS: B contact material: Copper alloy, with gold plate over nickel plate. Q contact material: Coin silver, silver plated. See page A-18 for additional contact materials.

CENTER CONTACTS & ALL TERMINALS: B contact material: Copper alloy, with gold plate over nickel plate. Q contact material: Copper alloy, silver plated. See page A-18 for additional contact materials.



TERMINAL SEAL: Epoxy.

HARDWARE: Nut & Locking Ring: Brass, nickel plated.
Lockwasher: Steel, nickel plated.

SWITCHES WITH STANDARD OPTIONS




7101SYZQE
SPDT





PART NUMBER	NO. POLES	POS. 1	POS. 2	POS. 3
7101SYZBE	SPDT	ON	NONE	ON
7101SYZGE		ON	NONE	ON
7101SYZQE		ON	NONE	ON
7103SYZQE		ON	OFF	ON
7105SYZQE		MOM.	OFF	MOM.
7107SYZQE		ON	OFF	MOM.
7108SYZQE		ON	NONE	MOM.

MOM. = Momentary

NOTE: For PC termination, replace 'Z' with 'C'.
For panel mounting information, see page A-9.
For PC mounting information, see page A-10.



7201SYZQE
DPDT





PART NUMBER	NO. POLES	POS. 1	POS. 2	POS. 3
7201SYZQE	DPDT	ON	NONE	ON
7203SYZQE		ON	OFF	ON
7205SYZQE		MOM.	OFF	MOM.
7207SYZQE		ON	OFF	MOM.
7208SYZQE		ON	NONE	MOM.
7211SYZQE		ON	ON	ON

MOM. = Momentary

NOTE: For PC termination, replace 'Z' with 'C'.
For panel mounting information, see page A-9.
For PC mounting information, see page A-10.



7301SYZQE
3PDT



PART NUMBER	NO. POLES	POS. 1	POS. 2	POS. 3
7301SYZQE	3PDT	ON	NONE	ON
7303SYZQE		ON	OFF	ON


NOTE: For PC termination, replace 'Z' with 'C'.
For panel mounting information, see page A-9.
For PC mounting information, see page A-10.

C&K 7000 Series Miniature Toggle Switches

SWITCHES WITH STANDARD OPTIONS

PART NUMBER	NO. POLES	POS. 1	POS. 2	POS. 3
7401SYZQE	4PDT			
7403SYZQE		ON	NONE	ON
7411SYZQE		ON	OFF	ON


NOTE: For PC termination, replace 'Z' with 'C'.
For panel mounting information, see page A-9.
For PC mounting information, see page A-10.



7401SYZQE
4PDT

PART NUMBER	NO. POLES	POS. 1	POS. 2	POS. 3
7201MD9AQE	DPDT			
		ON	NONE	ON
		ON	OFF	ON


NOTE: For PC mounting information, see page A-11.



7201MD9ABE
Horizontal Actuation
DPDT

PART NUMBER	NO. POLES	POS. 1	POS. 2	POS. 3
7301MD9ABE	3PDT			
		ON	NONE	ON
		ON	OFF	ON


NOTE: For PC mounting information, see page A-11.



7301MD9ABE
Horizontal Actuation
3PDT

PART NUMBER	NO. POLES	POS. 1	POS. 2	POS. 3
7201MD9AV2BE	2PDT			
		ON	NONE	ON
		ON	OFF	ON

NOTE: For PC mounting information, see page A-13.



7201MD9AV2BE
Vertical Actuation
DPDT

C&K 7000 Series Miniature Toggle Switches






A

Toggle

SWITCH FUNCTION



NO. POLES	MODEL NO.	UL/CSA** MODEL NO.	SWITCH FUNCTION			CONNECTED TERMINALS			SCHEMATIC	
			POS. 1	POS. 2	POS. 3	POS. 1	POS. 2	POS. 3		
										
SP	7101 (STD.)	U11	ON	NONE	ON	2-3	OPEN	2-1		
	7103 (STD.)	U13	ON	OFF	ON					
	7105	U15	MOM.	OFF	MOM.					
	7107	U17	ON	OFF	MOM.					
	7108	U18	ON	NONE	MOM.					
	7109	U19	NONE	ON	MOM.	N/A	2-3	2-1		SPDT
DP	7201 (STD.)	U21	ON	NONE	ON	2-3,5-6	OPEN	2-1,5-4		
	7203 (STD.)	U23	ON	OFF	ON					
	7205	U25	MOM.	OFF	MOM.					
	7207	U27	ON	OFF	MOM.					
	7208	U28	ON	NONE	MOM.					
	7209	U29	NONE	ON	MOM.	N/A	2-3,5-6	2-1,5-4		DPDT
	7211 (STD.)*	U211*	ON	ON	ON	2-3,5-6	2-3,5-4	2-1,5-4		
	7213*	U213*	ON	ON	MOM.					
7215*	U215*	MOM.	ON	MOM.						
3P	7301 (STD.)	U31	ON	NONE	ON	2-3,5-6,8-9	OPEN	2-1,5-4,8-7		
	7303	U33	ON	OFF	ON					
	7305	U35	MOM.	OFF	MOM.					
	7307	U37	ON	OFF	MOM.					
	7308	U38	ON	NONE	MOM.					
	7309	U39	NONE	ON	MOM.	N/A	2-3,5-6,8-9	2-1,5-4,8-7		3PDT
4P	7401 (STD.)	U41	ON	NONE	ON	2-3,5-6,8-9,11-12	OPEN	2-1,5-4,8-7,11-10		
	7403	U43	ON	OFF	ON					
	7405	U45	MOM.	OFF	MOM.					
	7407	U47	ON	OFF	MOM.					
	7408	U48	ON	NONE	MOM.					
	7409	U49	NONE	ON	MOM.	N/A	2-3,5-6,8-9,11-12	2-1,5-4,8-7,11-10		4PDT
	7411*	U411*	ON	ON	ON	2-3,5-6,8-9,11-12	2-3,5-4,8-9,11-10	2-1,5-4,8-7,11-10		
	7413*	U413*	ON	ON	MOM.					
	7415*	U415*	MOM.	ON	MOM.					


MOM. = Momentary

* Wiring for 3-way switch, see page L-29.

**U11-U415 model nos. with all options when ordered with G, L, M or Q contact material.


C&K 7000 Series Miniature Toggle Switches

ACTUATOR



S (STD.) .410" HIGH ¹

SP ANTIROTATION, .420" HIGH ^{2,3}




S actuator standard when ordered with C, W-W5, Z & Z3 terminations.

NOTE: Caps are available separately, see page L-10.

M (STD.) .200" HIGH ¹


MP ANTIROTATION, .200" HIGH ^{2,3}



M actuator standard when ordered with all terminations except C, W-W5, Z & Z3.


L, L1, L2 .840", .640", .550" HIGH ¹

LP, L1P, L2P ANTIROTATION, .840", .640", .550" HIGH ^{2,3}




OPTION CODE	DIM. "A"
L, LP	.840 (21,34)
L1, L1P	.640 (16,26)
L2, L2P	.550 (13,97)


P1 FLATTED WITH ANTIROTATION, .840" HIGH ^{2,3}



P3 (STD.) FLATTED WITH ANTIROTATION, .450" HIGH ^{2,3}




P4 FLATTED WITH ANTIROTATION, .250" HIGH ^{2,3}



Dress nut part number 709901201 supplied standard with threaded bushing. (Part number 709903201 with metric threaded bushings.)


T (STD.) .687" HIGH ^{1,2}

TP ANTIROTATION, .687" HIGH, 15/32 BUSHING ^{1,2,3}




T1 .460" HIGH ^{1,2}

T1P ANTIROTATION, .460" HIGH, 15/32 BUSHING ^{1,2,3}



T2P FLATTED, ANTIROTATION, .610" HIGH, 15/32 BUSHING ^{1,2,3}



Bushing option code not required unless CW splashproof bushing ordered. TP & T1P actuators not available with CW splashproof bushing. All TXX actuators not available on single pole models with A-A7, AW-AW4, R & R2 terminations.

Bushing option code not required. T2P actuator not available with CW splashproof bushing or single pole models with A-A7, AW-AW4, R & R2 terminations.

¹ L, L1, L2, M, S & TXX actuators not available with Y1 bushing.

² LP, L1P, L2P, MP, P1, P3, P4, SP & TXX actuators not available with D8 & H4 bushing.

³ Antirotation: Provides anti-push-in feature on actuator.


* Add .070 (1,78) for D, D8 & D9 bushings, subtract .020 (0,51) for H3 bushing.

OPTION CODE	ACTUATOR FINISH
NONE	(STD.) BRIGHT CHROME-With Nickel Plated Bushing
2	(STD.) BLACK
0	BRIGHT CHROME-With Black Bushing
S	SATIN CHROME

NOTE: Black hardware is supplied when either black actuators or bushings are specified. All hardware is available separately, see section L.




C&K 7000 Series Miniature Toggle Switches




Toggle

ACTUATOR




- K2** LOCKING LEVER, .704" HIGH (threaded)
K9 LOCKING LEVER, .704" HIGH (unthreaded)

- K12** LOCKING LEVER, .732" HIGH (threaded)
K19 LOCKING LEVER, .732" HIGH (unthreaded)



Replaces K, K8



Replaces K1, K18

OPTION CODE	ACTUATOR CAP FINISH
NONE	(STD.) NATURAL ALUMINUM—With Nickel Plated Bushing
0	(STD.) NATURAL ALUMINUM—With Black Bushing
2	BLACK ANODIZED ALUMINUM
3	RED ANODIZED ALUMINUM
7	BLUE ANODIZED ALUMINUM

Locking Positions



-01 Models
2 Position lock



-03 & -11 Models
3 Position lock



-05, -09 & -15 Models
1 Position lock



-07 & -13 Models
2 Position lock




-08 Models
1 Position lock

NOTE: To prevent accidental actuation, toggle must be lifted before being actuated. When released, toggle will lock in place. Overtightening mounting nut may cause actuator to bind.


Bushing option code not required unless CW splashproof bushing ordered.

L40 LEVER HANDLE WITHOUT CAP




No color choice required.

L41 PLASTIC LEVER HANDLE WITH ANTIROTATION AND CAP, P/N 4810




Finish: Matte (L41 & L42).

L42 PLASTIC LEVER HANDLE WITH ANTIROTATION AND CAP, P/N 4811



L3 PLASTIC, .840" HIGH

L3P ANTIROTATION, .840" HIGH



OPTION CODE	PLASTIC ACTUATOR COLORS
NONE	(STD.) No Actuator Color (L40 option)
2	(STD.) BLACK
1	WHITE
3	RED

* Add .070 (1,78) for D, D8 & D9 bushings, subtract .020 (0,51) for H3 bushing.


NOTE: Lever handle for L41 & L42 actuators supplied, but not installed. For interchangeability, order L40 actuator option and lever handles separately, see section L. L4X actuators not available with H4, Y1, Y4 bushings. Antirotation: Provides anti-'push-in' feature on actuator.

C&K 7000 Series Miniature Toggle Switches



Toggle
A

BUSHING



Y (STD.) .350" HIGH, THREADED, KEYWAY

Y9 .350" HIGH, UNTHREADED, KEYWAY

NONE NO BUSHING


D (STD.) .280" HIGH, THREADED, KEYWAY

D8 .280" HIGH, UNTHREADED, FLAT³


D9 .280" HIGH, UNTHREADED, KEYWAY

H (STD.) .296" HIGH, FLAT, THREADED, HIGH TORQUE^{1, 2}


H3 .315" HIGH, KEYWAY, THREADED, HIGH TORQUE^{1, 2}




No bushing choice required with KXX, TXX actuators. (exception: Specify CW if splashproof bushing desired).







D8 D, D9



Y bushing standard with C, W-W5, Z or Z3 terminations.



D9 bushing standard with all terminations except C, W-W5, Z or Z3. Add .070 (1, 78) to all actuators lengths with D, D8 & D9 bushings.










Subtract .020 (0, 51) from all actuator lengths for H3 bushing.

H4 8mm HIGH, KEYWAY, THREADED, METRIC HIGH TORQUE^{1, 2, 3}

Y1 .378" HIGH, KEYWAY, THREADED, HIGH TORQUE^{1, 2, 4}

Y3 8.9mm HIGH, KEYWAY, THREADED, METRIC



Y4 .378" HIGH, FLAT, THREADED, HIGH TORQUE^{1, 2, 5}





CW THREADED, SPLASHPROOF^{1, 2}

For T & T1 actuators.

For actuators other than T & T1.



IP67 Degree of protection, totally protected against dust, full-scale voltage protection, temporary immersion. Internal actuator seal standard. External bushing seal washer available from: Multi-Flex Seals, Inc., Hackensack, NJ. Part number: MFS-60064.



IP67 Degree of protection, totally protected against dust, full-scale voltage protection, temporary immersion. Internal actuator seal and external bushing seal washer standard.

OPTION CODE	BUSHING FINISH
NONE	(STD.) NICKEL on all bushings except 'D8' satin chrome.
2	BLACK

¹ Will withstand 12 in.-lbs. of torque with no distortion.

² CW, H, H3, H4, Y1 & Y4 bushings not available on single pole models with A4, R or R2 terminations.

³ D8 & H4 bushings available only with L, L1, L2, L3, M & S actuators.

⁴ Y1 bushing available only with LP, LXP, MP, PX & SP actuators.

⁵ Y4 bushing not available with L4X actuators.


NOTE: Two mounting nuts, locking ring and lockwasher supplied standard with threaded bushings. Black hardware is supplied when either black bushings or actuators are specified. Optional mounting nut and locking ring styles and finishes available, see section L.

PANEL MOUNTING


1/4 INCH BUSHING

METRIC BUSHING


15/32 INCH BUSHING




Without locking ring.




With standard locking ring.




With small locking ring.




Without locking ring.



With locking ring.



Without locking ring.




With standard locking ring.

C&K 7000 Series Miniature Toggle Switches

TERMINATIONS




Z (STD.) SOLDER LUG



SPDT thru 4PDT


Not available with K, L or M contact materials.

C (STD.) PC THRU-HOLE




SPDT thru 4PDT

PC MOUNTING




Z3 QUICK CONNECT



SPDT thru 4PDT

Not available with K, L or M contact materials.
Mating quick connector available, order part number 530100000.


W, W1, W3, W4, W5 WIRE WRAP




SPDT thru 4PDT

OPTION CODE	DIM 'A'
W	.750 (19,05)
W1	.964 (24,48)
W3	.425 (10,80)
W4	1.062 (26,97)
W5	1.305 (33,15)


A (STD.) RIGHT ANGLE, PC THRU-HOLE



7101MD9ABE
Horizontal Actuation
SPDT




Actuator Shown
In Pos. 1



Switch support with CW, H, H3, H4, Y1, Y4 bushings and KXX actuators.


Part No. Shown: 7101MHABE




SECTION A-A

Terminal Nos.
For Reference Only

A3 RIGHT ANGLE, SNAP-IN, PC THRU-HOLE




AW, AW1, AW3, AW4 RIGHT ANGLE, EXTENDED, PC THRU-HOLE



OPTION CODE	DIM 'A'
AW	.50 (12,7)
AW1	.72 (18,3)
AW3	.20 (5,1)
AW4	.83 (21,1)

PC MOUNTING







Not available with I seal option.
Terminal bend radii and lead-in manufacturing option.

C&K 7000 Series Miniature Toggle Switches

TERMINATIONS




A (STD.) RIGHT ANGLE, PC THRU-HOLE




7201MD9ABE
Horizontal Actuation
DPDT

A3 RIGHT ANGLE, SNAP-IN, PC THRU-HOLE




AW, AW1, AW4 RIGHT ANGLE, EXTENDED, PC THRU-HOLE







OPTION CODE	DIM 'A'
AW	.19 (4,8)
AW1	.40 (10,2)
AW4	.50 (12,7)

PC MOUNTING




Not available with I seal option.
Terminal bend radii and lead-in manufacturing option.

A (STD.) RIGHT ANGLE, PC THRU-HOLE




7301MD9ABE
Horizontal Actuation
3PDT

AW4 RIGHT ANGLE, EXTENDED, PC THRU-HOLE



PC MOUNTING



Not available with I seal option.
Terminal bend radii and lead-in manufacturing option.

C&K 7000 Series Miniature Toggle Switches


TERMINATIONS





A2 RIGHT ANGLE, PC THRU-HOLE, .156" PITCH



7101MHA2BE
Horizontal Actuation
SPDT




Actuator Shown In Pos. 1



Switch support with CW, H, H3, H4, Y1, Y4 bushings and KXX actuators.

Part No. Shown: 7101MHA2BE

PC MOUNTING




Not available with TXX actuators and I seal.
Terminal bend radii and lead-in manufacturing option.



A4 RIGHT ANGLE, PC THRU-HOLE, .156" PITCH




7101MD9A4BE
Horizontal Actuation
SPDT



Actuator Shown In Pos. 1




PC MOUNTING



NOTE: Termination options A4 & R2 are functionally identical and fit the same PC mounting pattern. The switches, however, are shifted relative to the mounting holes. Unlike the R2, the A4 option is available with any contact material and can be UL recognized and CSA certified. The PC pattern must clear switch support legs.



AV2 (STD.) VERTICAL RIGHT ANGLE, PC THRU-HOLE, .150" PITCH



7101MD9AV2BE
Vertical Actuation
SPDT



Actuator Shown In Pos. 1




SECTION A-A


AV3 VERTICAL RIGHT ANGLE, SNAP-IN, PC THRU-HOLE, .150" PITCH



Actuator Shown In Pos. 1




PC MOUNTING




Not available with I seal option.
Terminal bend radii and lead-in manufacturing option.

C&K 7000 Series Miniature Toggle Switches



TERMINATIONS




AV2 (STD.) VERTICAL RIGHT ANGLE, PC THRU-HOLE, .150" PITCH



Actuator Shown In Pos. 1





SECTION A-A




7201MD9AV2BE
Vertical Actuation
DPDT

AV3 VERTICAL RIGHT ANGLE, SNAP-IN, PC THRU-HOLE, .150" PITCH




PC MOUNTING





Not available with I seal option.
Terminal bend radii and lead-in manufacturing option.


AV2 (STD.) VERTICAL RIGHT ANGLE, PC THRU-HOLE, .150" PITCH



Actuator Shown In Pos. 1





SECTION A-A




7301MD9AV2BE
Vertical Actuation
3PDT

AV3 VERTICAL RIGHT ANGLE, SNAP-IN, .150" PITCH



PC MOUNTING




Not available with I seal option.
Terminal bend radii and lead-in manufacturing option.

C&K 7000 Series Miniature Toggle Switches


TERMINATIONS





AV2 (STD.) VERTICAL RIGHT ANGLE, PC THRU-HOLE,
.150" PITCH



7401MD9AV2BE
Vertical Actuation
4PDT





Actuator Shown In Pos. 1




SECTION A-A

AV3 VERTICAL RIGHT ANGLE, SNAP-IN, PC THRU-HOLE,
.150" PITCH



PC MOUNTING




Not available with I seal option.
Terminal bend radii and lead-in manufacturing option.



R RIGHT ANGLE WITH PCB




7101MD9RBE
Horizontal Actuation
SPDT



Actuator Shown In Pos. 1



PC MOUNTING




Not available with KXX & TXX actuators, CW, H, H3, H4, Y1 & Y4 bushings.
Contact makes on same side actuator thrown.



R2 RIGHT ANGLE WITH PCB




7101MD9R2BE
Horizontal Actuation
SPDT



Actuator Shown In Pos. 1



PC MOUNTING




Not available with KXX & TXX actuators, CW, H, H3, H4, Y1 & Y4 bushings.
Contact makes on opposite side actuator thrown.

C&K 7000 Series Miniature Toggle Switches


TERMINATIONS





A7 RIGHT ANGLE, PC THRU-HOLE,
.025" SQUARE, .200" PITCH



Actuator Shown In Pos. 1



SECTION A-A




7101MD9A7BE
Horizontal Actuation
SPDT



Not available with KXX & TXX actuators, H, H3, H4, Y1 & Y4 bushings. I seal option.
Terminal bend radii and lead-in manufacturing option. Available with B contact material only.

V2, V6, V7, V8 VERTICAL MOUNT, V-BRACKET

V21, V61, V71, V81 VERTICAL MOUNT, V-BRACKET, SNAP-IN



Actuator Shown In Pos. 1




7101MD9_BE
SPDT

OPTION CODE	DIM 'A'
V2, V21	.555 (14,10)
V6, V61	.460 (11, 68)
V7, V71	.630 (16, 00)
V8, V81	.953 (24, 21)



Not available with I seal option.

V2, V6, V7, V8 VERTICAL MOUNT, V-BRACKET

V21, V61, V71, V81 VERTICAL MOUNT, V-BRACKET, SNAP-IN



Actuator Shown In Pos. 1




7201MD9_BE
DPDT

OPTION CODE	DIM 'A'
V2, V21	.555 (14,10)
V6, V61	.460 (11, 68)
V7, V71	.630 (16, 00)
V8, V81	.953 (24, 21)

Not available with I seal option.

C&K 7000 Series Miniature Toggle Switches

TERMINATIONS




V2, V7, V8 VERTICAL MOUNT, V-BRACKET


V21, V71, V81 VERTICAL MOUNT, V-BRACKET, SNAP-IN




7301MD9_BE
3PDT




Actuator Shown In Pos. 1



Snap-In



PC MOUNTING



OPTION CODE	DIM 'A'
V2, V21	.555 (14,10)
V7, V71	.630 (16,00)
V8, V81	.953 (24,21)


Not available with I seal option.

V2, V7, V8 VERTICAL MOUNT, V-BRACKET


V21, V71, V81 VERTICAL MOUNT, V-BRACKET, SNAP-IN




7401MD9_BE
4PDT




Actuator Shown In Pos. 1



Snap-In



PC MOUNTING




OPTION CODE	DIM 'A'
V2, V21	.555 (14,10)
V7, V71	.630 (16,00)
V8, V81	.953 (24,21)


Not available with I seal option.

V3 (STD.), V4, V9 VERTICAL MOUNT, V-BRACKET


V31, V41, V91 VERTICAL MOUNT, V-BRACKET, SNAP-IN




7101MD9_BE
SPDT




Actuator Shown In Pos. 1



Snap-In



PC MOUNTING



OPTION CODE	DIM 'A'
V3, V31	.460 (11,68)
V4, V41	.630 (16,00)
V9, V91	1.150 (29,21)

Not available with I seal option.


C&K 7000 Series Miniature Toggle Switches

TERMINATIONS




V3 (STD.), V4, V9 VERTICAL MOUNT, V-BRACKET


V31, V41, V91 VERTICAL MOUNT, V-BRACKET, SNAP-IN




Actuator Shown In Pos. 1



Snap-In



PC MOUNTING




7201MD9_BE
DPDT

OPTION CODE	DIM 'A'
V3, V31	.460 (11,68)
V4, V41	.630 (16,00)
V9, V91	1.150 (29,21)


Not available with I seal option.

V4, V9 VERTICAL MOUNT, V-BRACKET


V41, V91 VERTICAL MOUNT, V-BRACKET, SNAP-IN




Actuator Shown In Pos. 1



Snap-In



PC MOUNTING




7301MD9_BE
3PDT

OPTION CODE	DIM 'A'
V4, V41	.630 (16,00)
V9, V91	1.150 (29,21)


Not available with I seal option.

V4, V9 VERTICAL MOUNT, V-BRACKET


V41, V91 VERTICAL MOUNT, V-BRACKET, SNAP-IN




Actuator Shown In Pos. 1



Snap-In



PC MOUNTING



7401MD9_BE
4PDT

OPTION CODE	DIM 'A'
V4 V41	.630 (16,00)
V9, V91	1.150 (29,21)

Not available with I seal option.

Toggle