

ENA-080312

• 30W



Features

- Full Range AC Input
- Short Circuit Protection
- Over Voltage Protection
- Over Load Protection

Electrical Specifications

- Input Voltage 100 ~ 240 VAC
Full Voltage Range
- Frequency 50 ~ 60 Hz
- Input current 1.5A Max.
- Holdup Time 10 ms @ Full Load
- High Efficiency 70% Min

Environmental Specifications

- Operating/Storage Temp. 0~40°C/-20~60°C
- Relative Humidity 5 ~ 95%
- Operating/Storage Altitude 10,000/50,000 FT
- MTBF 70,000 HRS

Output Specifications

| Voltage | Regulation | Min. | Max. | Maximum Peak to Peak Ripple & Noise |
|---------|------------|---------------|---------------|-------------------------------------|
| +12V | +/- 5% | 11.4V 0.0A | 12.6V 2.5A | 120 mVp-p |

Dimension (WxLxH)

- 120 x 61.5 x 38 (mm)
- 4.75 x 2.45 x 1.5 (inch)

Notes

- Specification subject to change without notice. All new processors support will be updated once official announced by vendors
- All company logo and legal name belong to original company. All copyright reserved by Enhance Electronics.
- One-Year Standard Warranty
- Last Update: 8/17/2005

ENA-080312

• 30W

Mechanical Drawing

Adaptor

