



# 3.3V CMOS 16-BIT TRANSPARENT D-TYPE LATCH WITH 3-STATE OUTPUTS AND 5 VOLT TOLERANT I/O

**IDT74LVC16373A**

## FEATURES:

- Typical  $t_{sk(o)}$  (Output Skew) < 250ps
- ESD > 2000V per MIL-STD-883, Method 3015; > 200V using machine model (C = 200pF, R = 0)
- $V_{cc} = 3.3V \pm 0.3V$ , Normal Range
- $V_{cc} = 2.7V$  to  $3.6V$ , Extended Range
- CMOS power levels ( $0.4\mu W$  typ. static)
- All inputs, outputs, and I/O are 5V tolerant
- Supports hot insertion
- Available in SSOP, TSSOP, and TVSOP packages

## DRIVE FEATURES:

- High Output Drivers:  $\pm 24mA$
- Reduced system switching noise

## APPLICATIONS:

- 5V and 3.3V mixed voltage systems
- Data communication and telecommunication systems



## DESCRIPTION:

The LVC16373A 16-bit transparent D-type latch is built using advanced dual metal CMOS technology. This high-speed, low-power latch is ideal for temporary storage of data. The LVC16373A can be used for implementing memory address latches, I/O ports, and bus drivers. The Output Enable and Latch Enable controls are organized to operate each device as two 8-bit latches or one 16-bit latch. Flow-through organization of signal pins simplifies layout. All inputs are designed with hysteresis for improved noise margin.


All pins of the LVC16373A can be driven from either 3.3V or 5V devices. This feature allows the use of this device as a translator in a mixed 3.3V/5V supply system.

The LVC16373A has been designed with a  $\pm 24mA$  output driver. This driver is capable of driving a moderate to heavy load while maintaining speed performance.

## FUNCTIONAL BLOCK DIAGRAM



## PIN CONFIGURATION



SSOP/ TSSOP/ TVSOP  
TOP VIEW

## ABSOLUTE MAXIMUM RATINGS<sup>(1)</sup>

| Symbol                             | Description                                                           | Max          | Unit |
|------------------------------------|-----------------------------------------------------------------------|--------------|------|
| V <sub>TERM</sub>                  | Terminal Voltage with Respect to GND                                  | −0.5 to +6.5 | V    |
| T <sub>STG</sub>                   | Storage Temperature                                                   | −65 to +150  | °C   |
| I <sub>OUT</sub>                   | DC Output Current                                                     | −50 to +50   | mA   |
| I <sub>IK</sub><br>I <sub>OK</sub> | Continuous Clamp Current,<br>V <sub>I</sub> < 0 or V <sub>O</sub> < 0 | −50          | mA   |
| I <sub>CC</sub><br>I <sub>SS</sub> | Continuous Current through each<br>V <sub>CC</sub> or GND             | ±100         | mA   |

### NOTE:

- Stresses greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

## CAPACITANCE (T<sub>A</sub> = +25°C, F = 1.0MHz)

| Symbol           | Parameter <sup>(1)</sup> | Conditions            | Typ. | Max. | Unit |
|------------------|--------------------------|-----------------------|------|------|------|
| C <sub>IN</sub>  | Input Capacitance        | V <sub>IN</sub> = 0V  | 4.5  | 6    | pF   |
| C <sub>OUT</sub> | Output Capacitance       | V <sub>OUT</sub> = 0V | 6.5  | 8    | pF   |
| C <sub>I/O</sub> | I/O Port Capacitance     | V <sub>IN</sub> = 0V  | 6.5  | 8    | pF   |

### NOTE:

- As applicable to the device type.

## PIN DESCRIPTION

| Pin Names | Description                       |
|-----------|-----------------------------------|
| x Dx      | Data Inputs                       |
| x LE      | Latch Enable Input (Active HIGH)  |
| x OE      | Output Enable Inputs (Active LOW) |
| x Q x     | 3-State Outputs                   |

## FUNCTION TABLE<sup>(1)</sup>

| Inputs |      |      | Outputs          |
|--------|------|------|------------------|
| x Dx   | x LE | x OE | x Q x            |
| H      | H    | L    | H                |
| L      | H    | L    | L                |
| X      | L    | L    | Q <sup>(2)</sup> |
| X      | X    | H    | Z                |

### NOTES:

- H = HIGH Voltage Level  
X = Don't Care  
L = LOW Voltage Level  
Z = High-Impedance
- Output level before the indicated steady-state input conditions were established.

## DC ELECTRICAL CHARACTERISTICS OVER OPERATING RANGE

Following Conditions Apply Unless Otherwise Specified:

Operating Condition:  $T_A = -40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$

| Symbol                              | Parameter                                              | Test Conditions                                                       |                                          | Min. | Typ. <sup>(1)</sup> | Max.     | Unit          |
|-------------------------------------|--------------------------------------------------------|-----------------------------------------------------------------------|------------------------------------------|------|---------------------|----------|---------------|
| $V_{IH}$                            | Input HIGH Voltage Level                               | $V_{CC} = 2.3\text{V}$ to $2.7\text{V}$                               |                                          | 1.7  | —                   | —        | V             |
|                                     |                                                        | $V_{CC} = 2.7\text{V}$ to $3.6\text{V}$                               |                                          | 2    | —                   | —        |               |
| $V_{IL}$                            | Input LOW Voltage Level                                | $V_{CC} = 2.3\text{V}$ to $2.7\text{V}$                               |                                          | —    | —                   | 0.7      | V             |
|                                     |                                                        | $V_{CC} = 2.7\text{V}$ to $3.6\text{V}$                               |                                          | —    | —                   | 0.8      |               |
| $I_{IH}$<br>$I_{IL}$                | Input Leakage Current                                  | $V_{CC} = 3.6\text{V}$                                                | $V_I = 0$ to $5.5\text{V}$               | —    | —                   | $\pm 5$  | $\mu\text{A}$ |
| $I_{OZH}$<br>$I_{OZL}$              | High Impedance Output Current<br>(3-State Output pins) | $V_{CC} = 3.6\text{V}$                                                | $V_O = 0$ to $5.5\text{V}$               | —    | —                   | $\pm 10$ | $\mu\text{A}$ |
| $I_{OFF}$                           | Input/Output Power Off Leakage                         | $V_{CC} = 0\text{V}$ , $V_{IN}$ or $V_O \leq 5.5\text{V}$             |                                          | —    | —                   | $\pm 50$ | $\mu\text{A}$ |
| $V_{IK}$                            | Clamp Diode Voltage                                    | $V_{CC} = 2.3\text{V}$ , $I_{IN} = -18\text{mA}$                      |                                          | —    | -0.7                | -1.2     | V             |
| $V_H$                               | Input Hysteresis                                       | $V_{CC} = 3.3\text{V}$                                                |                                          | —    | 100                 | —        | mV            |
| $I_{CCL}$<br>$I_{CCH}$<br>$I_{CCZ}$ | Quiescent Power Supply Current                         | $V_{CC} = 3.6\text{V}$                                                | $V_{IN} = \text{GND}$ or $V_{CC}$        | —    | —                   | 10       | $\mu\text{A}$ |
|                                     |                                                        |                                                                       | $3.6 \leq V_{IN} \leq 5.5\text{V}^{(2)}$ | —    | —                   | 10       |               |
| $\Delta I_{CC}$                     | Quiescent Power Supply Current Variation               | One input at $V_{CC} - 0.6\text{V}$ , other inputs at $V_{CC}$ or GND |                                          | —    | —                   | 500      | $\mu\text{A}$ |

### NOTES:

- Typical values are at  $V_{CC} = 3.3\text{V}$ ,  $+25^{\circ}\text{C}$  ambient.
- This applies in the disabled state only.

## OUTPUT DRIVE CHARACTERISTICS

| Symbol   | Parameter           | Test Conditions <sup>(1)</sup>          |                          | Min.           | Max. | Unit |
|----------|---------------------|-----------------------------------------|--------------------------|----------------|------|------|
| $V_{OH}$ | Output HIGH Voltage | $V_{CC} = 2.3\text{V}$ to $3.6\text{V}$ | $I_{OH} = -0.1\text{mA}$ | $V_{CC} - 0.2$ | —    | V    |
|          |                     | $V_{CC} = 2.3\text{V}$                  | $I_{OH} = -6\text{mA}$   | 2              | —    |      |
|          |                     | $V_{CC} = 2.3\text{V}$                  | $I_{OH} = -12\text{mA}$  | 1.7            | —    |      |
|          |                     | $V_{CC} = 2.7\text{V}$                  |                          | 2.2            | —    |      |
|          |                     | $V_{CC} = 3\text{V}$                    |                          | 2.4            | —    |      |
|          |                     | $V_{CC} = 3\text{V}$                    | $I_{OH} = -24\text{mA}$  | 2.2            | —    |      |
| $V_{OL}$ | Output LOW Voltage  | $V_{CC} = 2.3\text{V}$ to $3.6\text{V}$ | $I_{OL} = 0.1\text{mA}$  | —              | 0.2  | V    |
|          |                     | $V_{CC} = 2.3\text{V}$                  | $I_{OL} = 6\text{mA}$    | —              | 0.4  |      |
|          |                     |                                         | $I_{OL} = 12\text{mA}$   | —              | 0.7  |      |
|          |                     | $V_{CC} = 2.7\text{V}$                  | $I_{OL} = 12\text{mA}$   | —              | 0.4  |      |
|          |                     | $V_{CC} = 3\text{V}$                    | $I_{OL} = 24\text{mA}$   | —              | 0.55 |      |

### NOTE:

- $V_{IH}$  and  $V_{IL}$  must be within the min. or max. range shown in the DC ELECTRICAL CHARACTERISTICS OVER OPERATING RANGE table for the appropriate  $V_{CC}$  range.  
 $T_A = -40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ .

## OPERATING CHARACTERISTICS, $V_{CC} = 3.3V \pm 0.3V$ , $T_A = 25^\circ C$

| Symbol | Parameter                                                | Test Conditions           | Typical | Unit |
|--------|----------------------------------------------------------|---------------------------|---------|------|
| CPD    | Power Dissipation Capacitance per Latch Outputs enabled  | $C_L = 0pF$ , $f = 10MHz$ | 39      | pF   |
| CPD    | Power Dissipation Capacitance per Latch Outputs disabled |                           | 6       |      |

## SWITCHING CHARACTERISTICS<sup>(1)</sup>

| Symbol                               | Parameter                                       | V <sub>CC</sub> = 2.7V |      | V <sub>CC</sub> = 3.3V ± 0.3V |      | Unit |
|--------------------------------------|-------------------------------------------------|------------------------|------|-------------------------------|------|------|
|                                      |                                                 | Min.                   | Max. | Min.                          | Max. |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation Delay<br>xDx to xQx                 | —                      | 4.9  | 1.6                           | 4.2  | ns   |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation Delay<br>xLE to xQx                 | —                      | 5.3  | 2.1                           | 4.6  | ns   |
| t <sub>PZH</sub><br>t <sub>PZL</sub> | Output Enable Time<br>x $\overline{OE}$ to xQx  | —                      | 5.7  | 1.3                           | 4.7  | ns   |
| t <sub>PHZ</sub><br>t <sub>PLZ</sub> | Output Disable Time<br>x $\overline{OE}$ to xQx | —                      | 6.3  | 2.5                           | 5.9  | ns   |
| t <sub>SU</sub>                      | Set-up Time, data before LE↓ HIGH or LOW        | 1.7                    | —    | 1.7                           | —    | ns   |
| t <sub>H</sub>                       | Hold Time, data after LE↓ HIGH or LOW           | 1.2                    | —    | 1.2                           | —    | ns   |
| t <sub>w</sub>                       | Pulse Width LE HIGH                             | 3.3                    | —    | 3.3                           | —    | ns   |
| t <sub>sk(0)</sub>                   | Output Skew <sup>(2)</sup>                      | —                      | —    | —                             | 500  | ps   |


### NOTES:

- See TEST CIRCUITS AND WAVEFORMS.  $T_A = -40^\circ C$  to  $+85^\circ C$ .
- Skew between any two outputs of the same package and switching in the same direction.

## TEST CIRCUITS AND WAVEFORMS

### TEST CONDITIONS

| Symbol            | V <sub>CC</sub> <sup>(1)</sup> =3.3V±0.3V | V <sub>CC</sub> <sup>(1)</sup> =2.7V | V <sub>CC</sub> <sup>(2)</sup> =2.5V±0.2V | Unit |
|-------------------|-------------------------------------------|--------------------------------------|-------------------------------------------|------|
| V <sub>LOAD</sub> | 6                                         | 6                                    | 2 x V <sub>CC</sub>                       | V    |
| V <sub>IH</sub>   | 2.7                                       | 2.7                                  | V <sub>CC</sub>                           | V    |
| V <sub>T</sub>    | 1.5                                       | 1.5                                  | V <sub>CC</sub> / 2                       | V    |
| V <sub>LZ</sub>   | 300                                       | 300                                  | 150                                       | mV   |
| V <sub>HZ</sub>   | 300                                       | 300                                  | 150                                       | mV   |
| C <sub>L</sub>    | 50                                        | 50                                   | 30                                        | pF   |



Test Circuit for All Outputs

#### DEFINITIONS:

C<sub>L</sub> = Load capacitance: includes jig and probe capacitance.


R<sub>T</sub> = Termination resistance: should be equal to Z<sub>OUT</sub> of the Pulse Generator.

#### NOTES:

1. Pulse Generator for All Pulses: Rate ≤ 10MHz; t<sub>r</sub> ≤ 2.5ns; t<sub>f</sub> ≤ 2.5ns.
2. Pulse Generator for All Pulses: Rate ≤ 10MHz; t<sub>r</sub> ≤ 2ns; t<sub>f</sub> ≤ 2ns.

### SWITCH POSITION


| Test                                    | Switch            |
|-----------------------------------------|-------------------|
| Open Drain<br>Disable Low<br>Enable Low | V <sub>LOAD</sub> |
| Disable High<br>Enable High             | GND               |
| All Other Tests                         | Open              |




Output Skew - t<sub>SK</sub>(x)

#### NOTES:

1. For t<sub>SK</sub>(0) OUTPUT1 and OUTPUT2 are any two outputs.
2. For t<sub>SK</sub>(b) OUTPUT1 and OUTPUT2 are in the same bank.




Propagation Delay




Enable and Disable Times

#### NOTE:

1. Diagram shown for input Control Enable-LOW and input Control Disable-HIGH.



Set-up, Hold, and Release Times



Pulse Width

## ORDERING INFORMATION

| IDT | XX          | LVC | X        | XX     | XXXX        | XX      |                                                      |
|-----|-------------|-----|----------|--------|-------------|---------|------------------------------------------------------|
|     | Temp. Range |     | Bus-Hold | Family | Device Type | Package |                                                      |
|     |             |     |          |        |             | PV      | Shrink Small Outline Package                         |
|     |             |     |          |        |             | PA      | Thin Shrink Small Outline Package                    |
|     |             |     |          |        |             | PF      | Thin Very Small Outline Package                      |
|     |             |     |          |        | 373A        |         | 16-Bit Transparent D-Type Latch with 3-State Outputs |
|     |             |     |          | 16     |             |         | Double-Density with Resistors, $\pm 24\text{mA}$     |
|     |             |     | Blank    |        |             |         | No Bus-hold                                          |
|     | 74          |     |          |        |             |         | $-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$       |



**CORPORATE HEADQUARTERS**  
2975 Stender Way  
Santa Clara, CA 95054

**for SALES:**  
800-345-7015 or 408-727-6116  
fax: 408-492-8674  
www.idt.com

**for Tech Support:**  
logichelp@idt.com  
(408) 654-6459