

APT2012SGC

SUPER BRIGHT GREEN


### Features

- 2.0mmx1.25mm SMT LED, 0.75mm THICKNESS.
- LOW POWER CONSUMPTION.
- WIDE VIEWING ANGLE.
- IDEAL FOR BACKLIGHT AND INDICATOR.
- VARIOUS COLORS AND LENS TYPES AVAILABLE.
- PACKAGE : 2000PCS / REEL.
- RoHS COMPLIANT.

### Description

The Super Bright Green source color devices are made with Gallium Phosphide Green Light Emitting Diode.

### Package Dimensions



#### Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is  $\pm 0.1$  (0.004") unless otherwise noted.
3. Specifications are subject to change without notice.

## Selection Guide

| Part No.   | Dice                     | Lens Type   | Iv (mcd)<br>@ 20mA |      | Viewing<br>Angle |
|------------|--------------------------|-------------|--------------------|------|------------------|
|            |                          |             | Min.               | Typ. | θ1/2             |
| APT2012SGC | SUPER BRIGHT GREEN (GaP) | WATER CLEAR | 4                  | 15   | 120°             |

Note:

1. θ1/2 is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.

## Electrical / Optical Characteristics at TA=25°C


| Symbol                | Parameter                | Device             | Typ. | Max. | Units | Test Conditions |
|-----------------------|--------------------------|--------------------|------|------|-------|-----------------|
| $\lambda_{peak}$      | Peak Wavelength          | Super Bright Green | 565  |      | nm    | IF=20mA         |
| $\lambda_D$           | Dominant Wavelength      | Super Bright Green | 568  |      | nm    | IF=20mA         |
| $\Delta\lambda_{1/2}$ | Spectral Line Half-width | Super Bright Green | 30   |      | nm    | IF=20mA         |
| C                     | Capacitance              | Super Bright Green | 15   |      | pF    | VF=0V;f=1MHz    |
| VF                    | Forward Voltage          | Super Bright Green | 2.2  | 2.5  | V     | IF=20mA         |
| IR                    | Reverse Current          | Super Bright Green |      | 10   | uA    | VR= 5V          |

## Absolute Maximum Ratings at TA=25°C

| Parameter                       | Super Bright Green | Units |
|---------------------------------|--------------------|-------|
| Power dissipation               | 105                | mW    |
| DC Forward Current              | 25                 | mA    |
| Peak Forward Current [1]        | 140                | mA    |
| Reverse Voltage                 | 5                  | V     |
| Operating / Storage Temperature | -40°C To +85°C     |       |






Note:

1. 1/10 Duty Cycle, 0.1ms Pulse Width.




Super Bright Green

APT2012SGC



**APT2012SGC**


Reflow Soldering Profile For Lead-free SMT Process.




NOTES:

1. We recommend the reflow temperature 245°C(+/-5°C).The maximum soldering temperature should be limited to 260°C.
2. Don't cause stress to the epoxy resin while it is exposed to high temperature.
3. Number of reflow process shall be 2 times or less.

### Recommended Soldering Pattern (Units : mm)



### Tape Specifications (Units : mm)



## Remarks:

If special sorting is required (e.g. binning based on forward voltage, luminous intensity, or wavelength), the typical accuracy of the sorting process is as follows:

1. Wavelength:  $\pm 1\text{nm}$
2. Luminous Intensity:  $\pm 15\%$
3. Forward Voltage:  $\pm 0.1\text{V}$

Note: Accuracy may depend on the sorting parameters.