

P-Channel 20-V (D-S) MOSFET, Low-Threshold

PRODUCT SUMMARY

V_{DS} (V)	$R_{DS(on)}$ (Ω)	I_D (A) ^e
- 20	0.65 at $V_{GS} = - 4.5$ V	- 0.58
	0.85 at $V_{GS} = - 2.5$ V	- 0.5

FEATURES


- Halogen-free According to IEC 61249-2-21 Available
- TrenchFET® Power MOSFET
- ESD Protected: 3000 V



RoHS
COMPLIANT
HALOGEN
FREE
Available

APPLICATIONS


- Drivers: Relays, Solenoids, Lamps, Hammers, Displays, Memories
- Battery Operated Systems, DC/DC Converters
- Power Supply Converter Circuits
- Load/Power Switching-Cell Phones, Pagers



Marking Code: K4ywl

K4 = Part Number Code for TP0101K

y = Year Code
w = Week Code
l = Lot Traceability



Ordering Information: TP0101K-T1-E3 (Lead (Pb)-free)
TP0101K-T1-GE3 (Lead (Pb)-free and Halogen-free)

ABSOLUTE MAXIMUM RATINGS $T_A = 25^\circ\text{C}$, unless otherwise noted

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	- 20	V
Gate-Source Voltage	V_{GS}	± 8	
Continuous Drain Current ($T_J = 150^\circ\text{C}$) ^b	I_D	- 0.58	A
		- 0.46	
Pulsed Drain Current ^a	I_{DM}	- 2	
Continuous Source-Drain (Diode Current) ^b	I_S	- 0.3	W
Power Dissipation ^b	P_D	0.35	
		0.22	
Operating Junction and Storage Temperature Range	T_J, T_{stg}	- 55 to 150	$^\circ\text{C}$

Notes:

a. Pulse width limited by maximum junction temperature.

b. Surface Mounted on FR4 board, $t \leq 10$ s.

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Limits	Unit
Thermal Resistance, Junction-to-Ambient ^b	R_{thJA}	357	$^\circ\text{C/W}$

Notes:

a. Pulse width limited by maximum junction temperature.

b. Surface Mounted on FR4 board, $t \leq 10$ s.

SPECIFICATIONS $T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise noted

Parameter	Symbol	Test Conditions	Limits			
			Min.	Typ.	Max.	Unit
Static						
Drain-Source Breakdown Voltage	V _{DS}	V _{GS} = 0 V, I _D = - 10 μA	- 20			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = - 50 μA	- 0.5	- 0.7	- 1.0	
Gate-Body Leakage	I _{GSS}	V _{DS} = - 0 V, V _{GS} = ± 4.5 V			± 5	μA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = - 20 V, V _{GS} = 0 V			- 1	
		V _{DS} = - 20 V, V _{GS} = 0 V, T _J = 55 °C			- 10	
On-State Drain Current ^a	I _{D(on)}	V _{DS} ≤ - 5 V, V _{GS} = - 4.5 V	- 1.2			A
		V _{DS} ≤ - 5 V, V _{GS} = - 2.5 V	- 0.5			
Drain-Source On-State Resistance ^a	R _{DS(on)}	V _{GS} = - 4.5 V, I _D = - 0.58 A		0.42	0.65	Ω
		V _{GS} = - 2.5 V, I _D = - 0.5 A		0.64	0.85	
Forward Transconductance ^a	g _{fs}	V _{DS} = - 5 V, I _D = - 0.58 A		1300		mS
Diode Forward Voltage ^a	V _{SD}	I _S = - 0.3 A, V _{GS} = 0 V		- 0.9	- 1.2	V
Dynamic ^b						
Total Gate Charge	Q _g	V _{DS} = - 6 V, V _{GS} = - 4.5 V I _D ≅ - 0.58 A		1400	2200	pC
Gate-Source Charge	Q _{gs}			300		
Gate-Drain Charge	Q _{gd}			250		
Gate Resistance	R _g			150		Ω
Turn-On Time	t _{d(on)}	V _{DD} = - 6 V, R _L = 10 Ω I _D ≅ - 0.58 A, V _{GEN} = - 4.5 V, R _g = 6 Ω		25	35	ns
	t _r			30	45	
Turn-Off Time	t _{d(off)}			55	85	
	t _f			38	60	




Notes:

a. Pulse test; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.


b. Guaranteed by design, not subject to production testing.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




On-Resistance vs. Drain Current and Gate Voltage



Capacitance




Gate Charge




On-Resistance vs. Junction Temperature


TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage




Threshold Voltage



Gate Current vs. Gate-Source Voltage




Single Pulse Power, Junction-to-Ambient



* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified
Safe Operating Area, Junction-to-Ambient



TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?72692.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.