



MT3

3 WATT DC/DC CONVERTER, SINGLE & MULTIPLE OUTPUTS



FEATURES

- 5 SIDED METAL CASE
- WIDE INPUT VOLTAGES
- HIGH EFFICIENCY AND RELIABILITY
- SINGLE AND DUAL OUTPUTS
- REGULATED OUTPUTS
- INTERNAL EMI FILTER
- LOW OUTPUT RIPPLE AND NOISE
- SHORT CIRCUIT PROTECTION
- DIRECT PCB-SOLDERING
- INDUSTRY STANDARD PINOUT (IC-24P)
- LOW PROFILE, 10mm (0.39") HEIGHT
- REMOTE CONTROL FUNCTION
- (ULTRA-WIDE INPUT RANGE MODELS)
- FIVE YEAR WARRANTY

EMI

Complies with: CISPR CLASS A

ELECTRICAL SPECIFICATIONS

All specifications are typical at nominal input, full load

INPUT SPECIFICATIONS

Input Voltage
 Wide Range - 2:1..... 5V/12V/20V/24V/48VDC
 Ultra Wide Range - 4:1..... 9-36VDC, 18-72VDC
 Input Filter..... PI-Network

OUTPUT SPECIFICATIONS

Output Voltage Accuracy..... Wide Range - 2:1 $\pm 5\%$
 Ultra Wide Range - 4:1 $\pm 2\%$
 Over-Current Protection..... Built-in (Automatic Recovery)
 Ripple Wide range- 2:1 150 mVp-p (DC to 20MHz)
 Ultra Wide Range - 4:1 100 mVp-p (DC to 20MHz)
 Line Regulation..... 1.0% max.
 Line Filter..... Built-in
 Remote Control..... Built-in
 Load Regulation..... Wide Range - 2:1
 1% max. Single Output
 5% max. Dual Output
 Ultra Wide Range - 4:1
 5% max.

GENERAL SPECIFICATIONS

Isolation Voltage
 Primary to Secondary..... DC 500V/ 1min. 5mA
 Primary to Case..... DC 500V/ 1min. 5mA
 Secondary to Case..... DC 500V/ 1min. 5mA
 MTBF..... >1,000,000 hours
 Isolation Resistance..... Input-Output-Case 50M-ohms min.
 (Measured at 500 VDC)

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature -25°C ~ +71°C
 Case Temperature +91°C
 Temperature Coefficient..... $\pm 0.05\%$ / °C
 Humidity..... 30%~95% RH
 Storage Temperature..... Wide Range - 2:1 -25°C ~ +85°C
 Ultra Wide Range - 4:1 -40°C ~ +100°C

PHYSICAL SPECIFICATIONS

Case Material..... Nickel-Plated Steel
 Dual In-Line Pin Configuration

Series

MODEL	INPUT VOLTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT	EFF. TYP.	PIN TYPE
MT3-0503SI MT3-0505SI MT3-0512SI MT3-0512WI MT3-0515WI	5VDC (4.5 - 7V)	3.3VDC 5VDC 12VDC ± 12 VDC ± 15 VDC	650mA 500mA 240mA ± 120 mA ± 95 mA	69% 72% 74% 74% 74%	A
MT3-1203SI MT3-1205SI MT3-1212SI MT3-1212WI MT3-1215WI	12VDC (9.5-18V)	3.3VDC 5VDC 12VDC ± 12 VDC ± 15 VDC	750mA 550mA 250mA ± 125 mA ± 100 mA	71% 73% 78% 78% 78%	
MT3-2003SI MT3-2005SI MT3-2012SI MT3-2012WI MT3-2015WI	12/24VDC (10-30V)	3.3VDC 5VDC 12VDC ± 12 VDC ± 15 VDC	700mA 550mA 250mA ± 125 mA ± 100 mA	72% 75% 80% 80% 80%	
MT3-2403SI MT3-2405SI MT3-2412SI MT3-2412WI MT3-2415WI	24VDC (18-36V)	3.3VDC 5VDC 12VDC ± 12 VDC ± 15 VDC	750mA 550mA 250mA ± 125 mA ± 100 mA	76% 80% 82% 83% 83%	
MT3-4803SI MT3-4805SI MT3-4812SI MT3-4812WI MT3-4815WI	48VDC (36-72V)	3.3VDC 5VDC 12VDC ± 12 VDC ± 15 VDC	750mA 550mA 250mA ± 125 mA ± 100 mA	76% 80% 82% 82% 83%	

TYPE A: SINGLE OUTPUT

1, 24	INPUT + V
12, 13	INPUT - V
11, 14	OUTPUT + V
10, 15	OUTPUT - V
2, 23	NC
3, 22	NC

TYPE A: DUAL OUTPUT

1, 24	INPUT + V
12, 13	INPUT - V
11, 14	OUTPUT1 + V
10, 15	COMMON
2, 23	OUTPUT2 - V
3, 22	COMMON



NOTE:

All specifications typical and nominal / full load and 25°C unless otherwise noted.
Avoid sustained operation in overload or dead short conditions.
Specifications subject to changes without notice.

MODEL	INPUT VOLTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT	EEF. TYP.	PIN TYPE
MT3-DH05SI MT3-DH12SI MT3-DH15SI MT3-DH05WI MT3-DH12WI MT3-DH15WI	12/24VDC (9-36V)	5VDC 12VDC 15VDC ±5VDC ±12VDC ±15VDC	125-500mA 62-250mA 50-200mA ±62-250mA ±31-125mA ±25-100mA	80% 81% 81% 80% 81% 81%	B
MT3-HL05SI MT3-HL12SI MT3-HL15SI MT3-HL05WI MT3-HL12WI MT3-HL15WI	24/48VDC (18-72V)	5VDC 12VDC 15VDC ±5VDC ±12VDC ±15VDC	125-500mA 62-250mA 50-200mA ±62-250mA ±31-125mA ±25-100mA	82% 83% 83% 81% 82% 82%	

TYPE B: SINGLE	
1, 2	INPUT + V
23, 24	INPUT - V
13	OUTPUT + V
12	OUTPUT - V
10, 11, 15	NC
20	SHUTDOWN

TYPE B: DUAL	
1, 2	INPUT + V
23, 24	INPUT - V
15	OUTPUT + V
13	OUTPUT - V
10, 11	COMMON
12	NC
20	SHUTDOWN



NOTE:

All specifications typical and nominal / full load and 25°C unless otherwise noted.
 Avoid sustained operation in overload or dead short conditions.
 Specifications subject to changes without notice.

