

Plug-In Screw Connector System For Printed Circuit Boards — Series 110





Series 110 offers a lower profile and smaller spacing than series 120 and 121 plug-in connectors. Headers feature a flange mechanism to ensure proper mating. **Specifications. Center to Center Spacing:** 3.5 mm/0.138". **Insulating Material:** Polyamide, self extinguishing to UL 94, V-0, color grey. **Temperature Limits:** Short Time — 140°C/284°F, Continuous — 80°C/176°F, Low Limit — -40°C/-40°F. **Comparative Tracking Index:** CTI>600. **Oxygen Index Rating:** 33%. **Screw:** M2. U.L. File E69841 (8 A, 300 V, 30-16 AWG), CSA File LR24322 (8 A, 300 V, 28-16 AWG). Larger pole configurations are available on request.

Horizontal Plug

Stock No.	Mfr.'s Type	Poles	Center-Center Spacing		EACH
			mm	In.	
924-0600	110-A-111/02	2	3.50	.138	.62
924-0610	110-A-111/03	3	3.50	.138	.82
924-0620	110-A-111/04	4	3.50	.138	.98
924-0630	110-A-111/05	5	3.50	.138	1.53
924-0640	110-A-111/06	6	3.50	.138	1.70
924-0650	110-A-111/07	7	3.50	.138	1.85
924-0660	110-A-111/08	8	3.50	.138	2.10
924-0670	110-A-111/09	10	3.50	.138	2.45
924-0680	110-A-111/12	12	3.50	.138	2.80

Single Level Vertical Header

Stock No.	Mfr.'s Type	Poles	Center-Center Spacing		EACH
			mm	In.	
924-0618	110-M-221/02	2	3.50	.138	.23
924-0619	110-M-221/03	3	3.50	.138	.30
924-0620	110-M-221/04	4	3.50	.138	.37
924-0621	110-M-221/05	5	3.50	.138	.54
924-0622	110-M-221/06	6	3.50	.138	.60
924-0623	110-M-221/07	7	3.50	.138	.66
924-0624	110-M-221/08	8	3.50	.138	.75
924-0625	110-M-221/10	10	3.50	.138	.85
924-0626	110-M-221/12	12	3.50	.138	.98

— NEW —

Single Level Horizontal Header

Stock No.	Mfr.'s Type	Poles	Center-Center Spacing		EACH
			mm	In.	
924-0609	110-M-211/02	2	3.50	.138	.26
924-0610	110-M-211/03	3	3.50	.138	.34
924-0611	110-M-211/04	4	3.50	.138	.41
924-0612	110-M-211/05	5	3.50	.138	.60
924-0613	110-M-211/06	6	3.50	.138	.68
924-0614	110-M-211/07	7	3.50	.138	.77
924-0615	110-M-211/08	8	3.50	.138	.85
924-0616	110-M-211/10	10	3.50	.138	.98
924-0617	110-M-211/12	12	3.50	.138	1.15

Single Level 45 Degree Header


Stock No.	Mfr.'s Type	Poles	Center-Center Spacing		EACH
			mm	In.	
924-0627	110-V-211/02	2	3.50	.138	.28
924-0628	110-V-211/03	3	3.50	.138	.41
924-0629	110-V-211/04	4	3.50	.138	.54
924-0630	110-V-211/05	5	3.50	.138	.66
924-0631	110-V-211/06	6	3.50	.138	.81
924-0632	110-V-211/07	7	3.50	.138	.94
924-0633	110-V-211/08	8	3.50	.138	1.08
924-0634	110-V-211/10	10	3.50	.138	1.35
924-0635	110-V-211/12	12	3.50	.138	1.62

Horizontal Wire Entry

Stock No.	Mfr.'s Type	Poles	EACH
924-0636	797-A-111/02	2	.41
924-0637	797-A-111/03	3	.54
924-0638	797-A-111/04	4	.75
924-0639	797-A-111/05	5	.82
924-0641	797-A-111/06	6	1.23
924-0643	797-A-111/07	7	1.28
924-0644	797-A-111/08	8	1.38
924-0645	797-A-111/10	10	1.50
924-0646	797-A-111/12	12	1.65

Vertical Wire Entry

Stock No.	Mfr.'s Type	Poles	EACH
924-0647	797-A-121/02	2	.41
924-0648	797-A-121/03	3	.54
924-0649	797-A-121/04	4	.75
924-0651	797-A-121/05	5	.82
924-0653	797-A-121/06	6	1.23
924-0655	797-A-121/07	7	1.29
924-0657	797-A-121/08	8	1.38
924-0659	797-A-121/10	10	1.51
924-0661	797-A-121/12	12	1.64

Screwless Terminal Blocks For Printed Circuit Boards — Series 797

Horizontal Wire Entry

Stock No.	Mfr.'s Type	Poles	EACH
924-0647	797-A-121/02	2	.41
924-0648	797-A-121/03	3	.54
924-0649	797-A-121/04	4	.75
924-0651	797-A-121/05	5	.82
924-0653	797-A-121/06	6	1.23
924-0655	797-A-121/07	7	1.29
924-0657	797-A-121/08	8	1.38
924-0659	797-A-121/10	10	1.49
924-0661	797-A-121/12	12	1.64

Vertical Wire Entry

Stock No.	Mfr.'s Type	Poles	EACH
924-0647	797-A-121/02	2	.41
924-0648	797-A-121/		